i.safe MOBILE



android enterprise

recommended

ZONE 2/22 CL I / DIV 2

IS930.2

The IS930.2 is the tablet for use in ATEX Zones 2/22 and CLI/Div2. The 8" tablet is highly robust, powerful and offers many technical advantages: 8400 mAh Battery, Qualcomm Snapdragon SDM 660 processor, NFC, Android™ 10.

) Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.) i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google LLC. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth's is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi'e is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners.) © 2021 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1041MD01REV06_EN 0.5.2021





NEC500 approval:

Class I Div. 2 Groups A, B, C, D, T4

Class II Div. 2 Groups

GSM 850/900/1800/

26/28A/28B/29/30/66

TD-SCDMA: B34/B39

SDM660 Octa-Core Kryo Gold-Quad cores

2,2 GHz

1,8 GHz

WCDMA: UMTS B1/2/4/5/8 LTE-FDD: B1/2/3/4/5/7/8/12

with MFBI B13/14/17/20/25/

LTE-TDD: B38/B39/B40/B41

Qualcomm Snapdragon

Kryo Silver-Quad cores

64 GB internal memory

F, G, 135°C Class III Div. 2

1900 MHz

TECHNICAL FEATURES



ATEX approval: EX-Zone 2/22 Il 3G Ex ic IIC T4 Gc IP64 Il 3D Ex ic IIIC T135°C Dc IP6X



EAC approval: 2Ex ic IIC T4 Gc X Ex ic IIIC T135°C Dc X



2,4 GHz + 5 GHz: IEEE 802.11a/ b/g/n/ac/e/k/r/h with max. 8 connections hotspot



size: 237 x 156 x 22 mm, weight: 890 g



Near Field Communication



2 cameras: 13 MP AF rear camera and 5 MP front camera



IECEx approval: Ex-Zone 2/22 Ex ic IIC T4 Gc IP6X Ex ic IIIC T135°C Dc IP6X



Android 10



Bluetooth® 5



external memory microSD up to 128 GB



magnetic charging port



micro-SIM card



SOS key Loneworker protection LWP ready (third party application required, based on country specific regulations)

FURTHER FEATURES



waterproof: 1 hour up to 2 m, impervious to dust and microparticles



operation range from -20 $^{\circ}$ C to 60 $^{\circ}$ C



8" multi capacitive touchscreen with a resolution of 1200 x 1920 pixel, RugDisplay-Glass



usable with gloves



8400 mAh Battery



GPS, A-GPS, Glonass, Beidou, Galileo



Proximity, acceleration, light, barometer and magnetic sensor



Tablet with integrated battery, Adapter, Type C USB Cable, Magnetic Charger Cable, Quick Start Manual and Safety Instructions