



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX EPS 21.0043X** Page 1 of 3 [Certificate history:](#)
Status: **Current** Issue No: 0
Date of Issue: 2021-10-12
Applicant: **i.safe MOBILE GmbH**
i_Park Tauberfanken 10
97922 Lauda-Koenigshofen
Germany
Equipment: **IS360.2 intrinsically safe Smartphone**
Optional accessory:
Type of Protection: **Intrinsic safety**
Marking: Ex ic IIC T4 Gc
Ex ic IIIC T135°C Dc

Approved for issue on behalf of the IECEx
Certification Body:

Position:

Signature:
(for printed version)

Date:

Ulrich Feike
Certification Manager



1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

Bureau Veritas Consumer Products Services Germany GmbH
Businesspark A96
86842 Türkheim
Germany





IECEX Certificate of Conformity

Certificate No.: **IECEX EPS 21.0043X**

Page 2 of 3

Date of issue: 2021-10-12

Issue No: 0

Manufacturer: **i.safe MOBILE GmbH**
i_Park Tauberfanken 10
97922 Lauda-Koenigshofen
Germany

Additional
manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"
Edition:6.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[DE/EPS/ExTR21.0044/00](#)

Quality Assessment Report:

[DE/EPS/QAR12.0003/13](#)



IECEX Certificate of Conformity

Certificate No.: **IECEX EPS 21.0043X**

Page 3 of 3

Date of issue: 2021-10-12

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

Description of equipment:

The intrinsically safe and robust smartphone IS360.2 was developed for tough use in hazardous areas of zone 2 and 22. The IS360.2 with its handy shape and the amplified loudspeaker attached to the front is particularly suitable for push-to-talk applications.

Electrical data:

Power supply:

Replaceable LiPo battery $U_O = 3.8 \text{ V}$ ($U_{O_max} = 4.35 \text{ V}$) / 3000 mAh / 11.4 Wh

Interfaces:

The device supports an USB interface (USB-C; $U_m = 5.88 \text{ V}$) for charging and data transmission and an earphone jack (3.5 mm) for a wired head set. Both interfaces are covered by IP pluggers and are not allowed to be opened in ex-hazardous areas. In addition, two external charging contacts are available for the charging process ($U_m = 5.88 \text{ V}$). The contacts are intrinsically safe for gas and dust.

Furthermore, up to two SIM cards and one micro-SD card may be used in the corresponding slot in potentially explosive atmospheres. The internal electrical capacity of the SIM and SD card is negligible.

SPECIFIC CONDITIONS OF USE: YES as shown below:

The battery shall be charged outside explosion hazardous areas only.

The device must be protected from impacts with high impact energy, against excessive UV light emission and high electrostatic charge processes.

The permitted ambient temperature range is $-10 \text{ }^\circ\text{C}$ to $+50 \text{ }^\circ\text{C}$.